

# Air/screen cleaner

UC-1000 / -1250 / -1500

**westrup**

UC1.05.1604.GB



**The UC air/screen cleaner is especially designed for cleaning and grading many sorts of cereals and seeds to a very high standard**

In standard construction, the UC machines are delivered with the following features.

The machine is fitted with inlet with feed roll.

The aspiration system consists of pre-aspiration and final aspiration.

Pre-aspiration chamber is with rotary valve and outlet to chute to the sieveboat.

Final aspiration chamber is with rotary valve and outlet to chute from the sieveboat.

Further with false air regulation.

The screen system consists of one sieveboat with 4 screen layers (each 2 screen parts); 1<sup>st</sup> and 3<sup>rd</sup> layers are scalping; 2<sup>nd</sup> and 4<sup>th</sup> layers are grading/sand.

All screens are rubber ball cleaned.

The machine has fixed speed drive and motors; incl. valve pipe for mounting of fan (optional).

The machine is of steel construction with sieveboat of laminated wood.

**Special features:**

- ♦ Fan and motor
- ♦ Vibrator feeder (instead of feed roll)

	UC-1000	UC-1250	UC-1500
Motor, sieveboat	1.10 kW	1.50 kW	1.50 kW
Screen size L=800 mm x W	1000 mm	1250 mm	1500 mm
Screen area	6.40 m <sup>2</sup>	8.00 m <sup>2</sup>	9.60 m <sup>2</sup>
Estimated capacity on wheat	3.8 t/h	4.8 t/h	5.8 t/h

Please contact us for detailed information or meet us at [www.westrup.com](http://www.westrup.com)

**Westrup A/S**

Sorøvej 21, DK-4200 Slagelse

Tel. +45 5852 2564, Fax +45 5852 5251

[info@westrup.com](mailto:info@westrup.com)