

Modular cleaner

westrup

SD-1000 / -1250 / -1500 / -1750 / -2000

SD1.02.0502.GB



Machine shown with enclosure doors

The SD mid range modular cleaner is a very versatile cleaner applicable for many cleaning purposes

It is excellent to master pre-cleaning jobs at modern intake plants; it is also suitable for dressing of malting barley.

Estimated capacity on wheat is ranging from 50 t/h – 100 t/h.

The machine is assembled with modular components to make up a cleaner to suit very specific requirements.

The great advantage of the modular system is that it also offers the capability of upgrading the machine according to future requirements.

The feeding apparatus can be in construction with feed roll, with feed roll and straw band, with feed roll and straw drum, or with vibratory feeder.

Pre-aspiration can be done in a channel with fixed or variable depth, in a chamber with standard air system or with air recirculation.

Aspiration can also be done in a chamber with one or two waste augers.

Final aspiration can be done in a channel with variable or fixed depth.

The sieve section consists of one sieveboat with fixed or variable screen inclination and different number of screen layers.

The machine is of steel construction with sieveboats of laminated wood.

Screen systems:	Screen area:				
	SD-1000	SD-1250	SD-1500	SD-1750	SD-2000
E26 / E27 – 2 x 2 layers	8.0 m ²	10.0 m ²	12.0 m ²	14.0 m ²	16.0 m ²
E30 – 4 parallel layers	8.0 m ²	10.0 m ²	12.0 m ²	14.0 m ²	16.0 m ²
E32 – 4 layers with various flows	8.0 m ²	10.0 m ²	12.0 m ²	14.0 m ²	16.0 m ²
E28 – 3 x 2 layers	12.0 m ²	15.0 m ²	18.0 m ²	21.0 m ²	24.0 m ²
E40 – 2 x 2 layers	9.6 m ²	12.0 m ²	14.4 m ²	16.8 m ²	19.2 m ²

Please contact us for detailed information or meet us at www.westrup.com

Westrup A/S

Box 127, Sorøvej 21, DK-4200 Slagelse
 Tel. +45 5852 2564, Fax +45 5852 5251
info@westrup.com