KA7.12.1811.GB

KA-3300 / -4400 / -5500



Photo shows KA-4400/-5500 with outlet transitions (option)

The KA high capacity gravity separator is used for fine grading and impurity separation of products with identical particle size but with differences in density

Gravity separation is often the only method to achieve the purity required and it is therefore used where traditional cleaning methods by air, screen, and indented cylinder prove not to be effective enough.

For capacity and all other specific information see the back page.

The gravity separator offers the below features:

- ° Inlet with manually adjustable capacity shutter.
- Oscillating grading deck with exchangeable air distribution plate and standard covering for grain (ripple deck).

- Outlet section with fixed outlet gates and manually adjustable outlet openings.
- Adjustment of deck speed by frequency converter.
- Hydraulic adjustment of deck inclinations by electrical pump.
- ° Air intake with filter cloth.
- ° Deck change from the side of the machine.
- ° Integrated fan.
- ° Drive and motors.

The machine is of steel construction with grading deck of aluminum.

Options:

- Dust hood over the entire deck
- ° Dust hood over 1/3 of the deck
- ° Outlet transitions
- ° PLC control cabinet with memory
- ° Deck with covering for small seeds

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions



GRAVITY SEPARATOR KA-3300 / -4400 / -5500

TECHNICAL SPECIFICATIONS:

	KA-3300	KA-4400	KA-5500
Deck area m²	2.4	3.4	6.1
Capacity t/h	7	12	18
Motor for deck speed kW	3	3	3
Motor for integrated fan kW	15	22	30
Motor for electrical pump kW	0.18	0.18	0.18

Capacity: estimate (guideline) based on fine cleaned wheat

DISTINGUISHING ADVANTAGES:

- ° Grading deck with manually adjustable outlet openings for splitting the product into the required fractions
- Easy setting of guide plates in the prime product outlet hopper ensuring a very sharp separation of a wide range of products
- Highly efficient air system with integrated fan ensuring a uniform air distribution across the entire grading deck and a good separation of heavy as well as light particles in one operation
- ° Easily and quickly exchangeable grading deck from the side of the machine
- ° Easy clean-down when changing from one product to another
- ° In right or left hand construction to suit individual plant layouts
- ° Low maintenance costs



Photo shows KA-4400/-5500 with outlet transitions [option]