







The VPM-6 is a palletizer suitable for packers who require more capacity and set higher standards for the stacking result. The machine is standardly equipped with a three-sided stacking bin enclosing the pallet and ensuring an accurate stack of the product.

This model has two standard stacking bins and can be manually adjusted to the pallet sizes required, i.e. Euro, block or sea pallet ($1200 \times 800 / 1000 / 1600 \text{ mm}$). Depending on the stacking height required, a stock of empty pallets can be placed in the stacking bin.

Conveyor belts and / or a vertical lift with automatic accumulation, transport the bags up into the palletizer towards the manipulator equipped with centring flaps. These ensure an accurate positioning of the bags on the pallet.

Specifications:

Capacity Maximum 10 bags / min.

Pallet sizes Standardly suitable for several pallet sizes:

- 1200 x 800 / 1000 / 1600 mm

-48 x 40 / 60 "

Bag sizes 10 - 50 kg

(approx. 320 x 520 mm - approx. 590 x 880 mm)

Pallet infeed / outfeed Forklift

Stacking height Maximum 2500 mm, including pallet

Formation doors No

Stacking bin 3-sided closed

Operation Touchscreen

Stacking patterns 10 freely programmable, each including maximum

16 closing layers

Air consumption - Minimum operating pressure: 8 bar

- Suction capacity required: 80 l / min.

Power 230 / 400 VAC + N + PE, 50 Hz; 3 x 25 A

Safety - Walk-in protection and screening at the outfeed side

- The machine is standardly equipped with full screening

Options - Several pallet sizes

- 4-sided closed stacking bin

medium capacity

• accurate stack of the product

two stacking bins

www.verbruggen.nl

DODÁVÁ A SERVIS PROVÁDÍ:

AGROMEGA spol. s r.o.

Tyršova 237 570 01 Litomyšl Česká republika tel: +420 461 618 660

+420 461 618 661

fax: +420 461 618 670

agromega@agromega.cz www.agromega.cz Verbruggen Emmeloord BV Bouwerskamp 13 Emmeloord The Netherlands T: +31 (0)527 62 02 32 info@verbruggen.nl