

Fine cleaner

AP-1000 / -1250 / -1500

westrup

AP1.06.1601.GB



The AP high performance cleaner is designed for fine cleaning of cereals

Estimated capacity on wheat is 9 t/h for AP-1000, 11 t/h for AP-1250, and 13 t/h for AP-1500.

In standard construction the AP machines are delivered with the following features.

The feeding apparatus is with weightloaded spreading valve and feed roll.

The aspiration system consists of a pre-aspiration chamber and a final aspiration chamber, both with waste auger.

The screen system consists of two sieveboats where the upper sieveboat contains 2 parallel screen layers with 4° screen inclination and the lower boat contains 3 parallel screen layers with 5° inclination.

Each screen layer consists of 3 single screens and all screens are rubber ball cleaned.

With fixed speed drive, motor, and valve pipe optional.

The machine is of steel construction with sieveboats of laminated wood.

Special features:

- ♦ Fan and motor

	AP-1000	AP-1250	AP-1500
Motor, sieveboats	2.2 kW	2.2 kW	2.2 kW
Screen size L=800 mm x W	1000 mm	1250 mm	1500 mm
Screen area	12 m ²	15 m ²	18 m ²
Weight	1825 kg	2145 kg	2450 kg



Please contact us for detailed information or meet us at www.westrup.com

Westrup A/S

Sorøvej 21, DK-4200 Slagelse

Tel. +45 5852 2564, Fax +45 5852 5251

info@westrup.com